



Performance Guide

Represents Typical Values Only

Dull Silver Laminated Foil Perm/40#

Item # D1023

FACE

An acrylic top coated laminated foil designed for printing with water and solvent based inks. A thin layer of foil is laminated to a 60# coated paper stock.

Caliper: .036" +/- 10%

Basis Weight	73#		#/3300ft ²
Tensile Strength (MD,CD)	35	21	grams
Break Elongation (MD,CD)	64	68	grams

ADHESIVE

Hot melt aggressive adhesive designed to offer excellent initial tack on various packaging substrates including corrugated and plastics.

Caliper: .0007" +/- 10%

Application Temperature Range: +40F to +120F

Service Temperature Range: -50F to +150F

	Loop Tack ₁	Shear ₂	Peel Adhesion ₃
Stainless Steel	PT	>4hours	PT
HDPE	n/a	n/a	n/a

LINER

A moisture stabilized 2.5mil bleach super calendered kraft paper stock, offering excellent die cutting and matrix stripping.

Caliper : .0025"

Basis Weight: 40#

CONSTRUCTION CALIPER

.0068" +/- 10%

Shelf life: 1 year stored at 72°F and 50% RH

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

Paper Resources, Inc. - 608 Rye Beach Road - Huron, OH 44839

800-813-8907

www.paperresources.com